

USG MARS™ PLANKS/USG MARS™ HIGH-NRC PLANKS AND LARGE SIZES

CLIMAPLUS™ PERFORMANCE WITH PLANT-BASED BINDER



USG Mars™ High-NRC Planks
with ClimaPlus™ Performance/
USG Donn® Brand DX*/DXL™
Acoustical Suspension System

Photo this page:
© Andrew Latreille
Architects: Perkins+Will/KRA/Group2

TO ORDER SAMPLES,
GO TO USG.COM OR CGCINC.COM



Flat White
050

FEATURES AND BENEFITS

- Highest NRC (0.90) mineral fiber plank offering available.
- High light-reflective finish (LR-0.90) reduces light fixtures and energy use.
- Washable and scrubbable finish.
- Impact and scratch resistant.
- Available in Optimized Recycled Content formulations to help maximize LEED recycled content contribution.
- Nondirectional, monolithic visual reduces installation time and waste.
- ClimaPlus™ 30-year limited system warranty against visible sag, mold and mildew.
- Balanced Acoustics. High-NRC and High-CAC.
- GREENGUARD Gold certified for low-emitting performance.

APPLICATIONS

- Offices
- Classrooms
- Healthcare
- Corridors
- Reception and lobby areas
- Convention halls and concourses

SUBSTRATE

- Wet-formed mineral fiber

Fine-Textured Panel

USG MARS™ PLANKS/USG MARS™ HIGH-NRC PLANKS AND LARGE SIZES

CLIMAPLUS™ PERFORMANCE WITH PLANT-BASED BINDER

ORDER SAMPLES/LITERATURE
USG: samplitt@usg.com
fax: 888 874-2348 | usg.com
CGC: contact Sales Representative

FOR MOST UP-TO-DATE
TECHNICAL INFORMATION
AND LEED REPORT TOOL
usgdesignstudio.com
cgcdesignstudio.com

TECHNICAL SERVICES
800 USG.4YOU (874-4968)



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS:
ULCOM/GG
UL2818



UL Classified

Edge	Panel Size ⁴	Fire Rating	Item No.	NRC	CAC Min.	LR ²	Color	Grid Options	VOC Emissions	Anti-Mold & Mildew/Sag Resistance	Recycled Content ¹	Panel Cost
SQ 	2'x5'x3/4"	Class A	86221	0.75	35	0.90	White	A,B	Low		69%	\$\$
	2'x6'x3/4"	Class A	86223	0.75	35	0.90	White	A,B	Low		69%	\$\$
SLT 	2'x5'x3/4"	Class A	86161	0.75	35	0.90	White	C	Low		69%	\$\$
	2'x6'x3/4"	Class A	86166	0.75	35	0.90	White	C	Low		69%	\$\$
	2'x6'x3/4"	Class A	86166HRC	0.70	35	0.90	White	C	Low		81%	\$\$
FLB 	2'x5'x3/4"	Class A	88984	0.75	35	0.90	White	D,E,F,G	Low		69%	\$\$
	2'x6'x3/4"	Class A	88996	0.75	35	0.90	White	D,E,F,G	Low		69%	\$\$
	2'x6'x3/4"	Class A	88996HRC	0.70	35	0.90	White	D,E,F,G	Low		81%	\$\$
SQ 	2'x5'x1"	Class A	89673	0.90	30	0.90	White	A,B	Low		66%	\$\$
	2'x6'x1"	Class A	89674	0.90	30	0.90	White	A,B	Low		66%	\$\$
	2'x5'x7/8"	Class A	89662	0.85	35	0.90	White	A,B	Low		65%	\$\$
	2'x6'x7/8"	Class A	89663	0.85	35	0.90	White	A,B	Low		65%	\$\$
	2'x5'x7/8"	Class A	86350	0.80	35	0.90	White	A,B	Low		65%	\$\$
	2'x6'x7/8"	Class A	86360	0.80	35	0.90	White	A,B	Low		65%	\$\$

USG MARS™
PLANKS

USG MARS™
HIGH-NRC PLANKS
Plant-Based Binder

Low Emissions (VOC)
Third party (GREENGUARD Gold) certified for low-emitting performance, meets California Department of Public Health's (CDPH) Standard Method v1.1 - 2010 (CA Section 01350). 'Certificates of Compliance' for Low VOC Emissions are available on usg.com and at productguide.ulenvironment.com.

ClimaPlus™ Warranty Performance³
Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sag-resistance performance.

High Recycled Content
Classified as containing greater than 50% total recycled content. Total recycled content is based on product composition of postconsumer and preconsumer (postindustrial) recycled content per FTC guidelines.

USG MARS™ PLANKS/USG MARS™ HIGH-NRC PLANKS AND LARGE SIZES

CLIMAPLUS™ PERFORMANCE WITH PLANT-BASED BINDER

ORDER SAMPLES/LITERATURE
 USG: samplit@usg.com
 fax: 888.874.2348 | usg.com
 CGC: contact Sales Representative
 usgdesignstudio.com
 cgcdesignstudio.com

TECHNICAL SERVICES
 800.USG.4YOU (874-4968)



PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS:
 ULCOM/GG
 UL2818



UL Classified

Edge	Panel Size ⁴	Fire Rating	Item No.	NRC	CAC Min.	LR ²	Color	Grid Options	VOC Emissions	Anti-Mold & Mildew/Sag Resistance	Recycled Content ¹	Panel Cost
SLT 	2'x5'x1"	Class A	89675	0.90	30	0.90	White	C	Low		66%	\$\$
	2'x6'x1"	Class A	89676	0.90	30	0.90	White	C	Low		66%	\$\$
	2'x5'x7/8"	Class A	89664	0.85	35	0.90	White	C	Low		65%	\$\$
	2'x6'x7/8"	Class A	89665	0.85	35	0.90	White	C	Low		65%	\$\$
	2'x5'x7/8"	Class A	89650	0.80	35	0.90	White	C	Low		65%	\$\$
	2'x6'x7/8"	Class A	89660	0.80	35	0.90	White	C	Low		65%	\$\$
FLB 	2'x5'x1"	Class A	89677	0.90	30	0.90	White	D,E, F,G	Low		66%	\$\$
	2'x6'x1"	Class A	89678	0.90	30	0.90	White	D,E, F,G	Low		66%	\$\$
	2'x5'x7/8"	Class A	89667	0.85	35	0.90	White	D,E, F,G	Low		65%	\$\$
	2'x6'x7/8"	Class A	89668	0.85	35	0.90	White	D,E, F,G	Low		65%	\$\$
	2'x5'x7/8"	Class A	89550	0.80	35	0.90	White	D,E, F,G	Low		70%	\$\$
	2'x6'x7/8"	Class A	89670	0.80	35	0.90	White	D,E, F,G	Low		70%	\$\$

Low Emissions (VOC)
 Third party (GREENGUARD Gold) certified for low-emitting performance, meets California Department of Public Health's (CDPH) Standard Method v1.1 - 2010 (CA Section 01350). *Certificates of Compliance* for Low VOC Emissions are available on usg.com and at productguide.ulenvironment.com.

ClimaPlus™ Warranty Performance³
 Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sag-resistance performance.

High Recycled Content
 Classified as containing greater than 50% total recycled content. Total recycled content is based on product composition of postconsumer and preconsumer (postindustrial) recycled content per FTC guidelines.

USG MARS™
 HIGH-NRC PLANKS CONT.
 Plant-Based Binder

USG MARS™ PLANKS/USG MARS™ HIGH-NRC PLANKS AND LARGE SIZES

CLIMAPLUS™ PERFORMANCE WITH PLANT-BASED BINDER

ORDER SAMPLES/LITERATURE
USG: samplitt@usg.com
fax: 888 874-2348 | usg.com
CGC: contact Sales Representative

FOR MOST UP-TO-DATE
TECHNICAL INFORMATION
AND LEED REPORT TOOL
usgdesignstudio.com
cgcdesignstudio.com

TECHNICAL SERVICES
800 USG.4YOU (874-4968)



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS:
ULCOM/GG
UL2818

GRID PROFILE OPTIONS



A USG DX [®] /DXL [™]	B USG DXW [™]	C USG DX [®] /DXL [™]	D USG Centricitee [™] DXT [™]	E USG Finline [®] DXF [™]	F USG Finline [®] 1/8 DXFF [™]	G USG Identitee [®] DXI [™]

PHYSICAL DATA/ FOOTNOTES

Product literature
Data sheet: SC2509

ASTM E1264 classification
Type IV, Form 1 and 2, Pattern E, G

**ASTM E84 and CAN/ULC S102
surface-burning characteristics**
Class A
Flame spread: 25 or less
Smoke developed: 50 or less

Weight
0.73 lb./sq. ft. (3/4" panels)
1.21 lb./sq. ft. (7/8" panels)
1.27 lb./sq. ft. (1" panels)

Online tools
usgdesignstudio.com or cgcdesignstudio.com

Thermal resistance
R-2.2 (3/4" panel)

Maximum backloading
See *USG 30-Year Limited System Warranty Commercial Applications (SC2102)*.

Maintenance
Can be cleaned easily with a soft brush or vacuum. To clean panel, use a clean, white cloth with water or a mild detergent and wipe surface. To disinfect panel, lightly spray surface and wipe clean with a clean, white cloth.

Metric sizes available
Contact sales for minimum quantities and lead times.

- Notes**
- For details, see LEED report tool at usgdesignstudio.com or cgcdesignstudio.com.
 - LR values are shown as averages.
 - Panel face and back surfaces treated with a proprietary, broad-spectrum antimicrobial additive that inhibits and retards the growth of mold and mildew. For details, see *USG 30-Year Limited System Warranty Commercial Applications (SC2102)* and *ClimaPlus™ Ceilings Certification of Performance (SC2451)*.
 - Stabilizer bar required if opening $\geq 60"$. For more information about stabilizer bars, please refer to *Plank and Large Panel Stabilizer Bars Application Guide (IC592)*.

Notice
The information in this document is subject to change without notice. CGC Inc. or USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document.

SC2509/rev. 11-16
© 2016 USG Corporation and/or its affiliates. All rights reserved. Printed in U.S.A.

Manufactured by
USG Interiors, LLC
550 West Adams Street
Chicago, IL 60661

The trademarks USG, CGC, CENTRICITEE, CLIMAPLUS, DONN, DX, DXF, DXFF, DXI, DXL, DXT, DXW, FINELINE, IDENTITEE, MARS, IT'S YOUR WORLD. BUILD IT., the USG/CGC logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

